

# Thermocast Installation Guidelines

## Important! – Before you Begin:

Read all instructions carefully before beginning installation. Remove the sink from its original carton and inspect it for damage. Return the sink to its protective carton until you are ready to place it into position in the countertop. Inspect your faucet hardware to insure that all components exist for a successful installation as outlined in the faucet and/or hardware installation guide. Inspect the waste and supply lines and replace if necessary.

## SELF RIMMING INSTALLATION *con't*

STEP NINE: Mount the faucet hardware on the sink following the manufacturer's instructions.

STEP TEN: Install the drain in accordance with the manufacturers instructions using Plumbers Putty following the manufacturer's instructions. Note: Silicone Sealant or any other sealants other than Plumbers Putty should not be used as a replacement for Plumbers Putty. Apply a thin, continuous bead of 100% silicone sealant to the underside outer perimeter of sink approximately 1/4" inside the perimeter and carefully position the sink in the opening. Remember that the sink rests on a layer of silicone sealant, not dry fitted to the countertop.

STEP ELEVEN: Verify that the sink has not moved out of position and immediately remove any excess sealant filling any remaining voids as needed.



STEP TWELVE: Allow the sealant to cure at least 1 hour before proceeding.

STEP THIRTEEN: Install the garbage/waste disposer, if applicable, following manufacturer's instructions.

STEP FOURTEEN: Connect the drain assembly.

STEP FIFTEEN: Connect the faucet supply lines following the faucet manufacturer's instructions.

STEP SIXTEEN: Carefully turn on the water supply lines, then turn faucet on and check faucet, drain, and drain assembly for leaks to insure a completed successful installation of your new Thermocast Cast Acrylic Sink.



## UNDER COUNTER INSTALLATION:

When planning to use a Thermocast sink in an under counter installation please check style and size before authorizing cutting of the countertop. For under mounting to granite or marble or solid surface materials, contact your granite-marble-solid surface fabricator for installation requirements and proper fasteners. Under counter installation kits are available, but not required or necessary by all professional fabricators. Please contact Thermocast Sales Support for details regarding under counter installation kits.

## ADDITIONAL ACCESSORY HOLES:

Please contact the Thermocast Sales Support Center for questions and/or instructions on adding accessory holes to your new Thermocast sink.

# Thermocast®

(A DIVISION OF INTERNATIONAL THERMOCAST CORPORATION)

308 Bell Park Drive • Woodstock, Georgia U.S.A.

Sales Support Center : 678-445-2022

[www.thermocastsinks.com](http://www.thermocastsinks.com)